"Die-Sinking EDM Machining of HAYNES HR-160 alloy: A Comprehensive Analysis of Machinability Characteristics"

SYNOPSIS

SUBMITTED IN PARTIAL FULFILLMENT OF THE REQUIREMENTS FOR THE AWARD OF A DEGREE

OF

DOCTOR OF PHILOSOPHY

IN ENGINEERING

DEPARTMENT OF MECHANICALENGINEERING

SUBMITTED TO

YBN University

Rajaulatu, Namkum, Ranchi-834010, Jharkhand, India

Session:- 2022-2025

SUPERVISOR

DR. ANJANI KUMAR SINGH

ASSISTANT PROFESSOR,
DEPARTMENT OF MECHANICAL ENGINEERING,
SCHOOL OF ENGINEERING AND TECHNOLOGY
YBN UNIVERSITY, RANCHI-834010.

RESEARCH SCHOLAR

CHANDAN KUMAR
ENROL. NO. 2203236,
DEPT OF MECHANICAL ENGINEERING
SCHOOL OF ENGINEERING AND TECHNOLOGY
YBN UNIVERSITY, RANCHI.

CO-SUPERVISOR

DR. ARVIND KUMAR

ASSISTANT PROFESSOR,
MECHANICAL ENGINEERING DEPARTMENT
RTC INSTITUTE OF TECHNOLOGY, RANCHI-835219.

CONTENTS

SL. NO.	SUBJECT	PAGE NO.
1	Introduction	3-4
2	Review of Literature	4-5
3	Objective of the study	5-7
4	Significance of the study	7-8
5	Study area	8
6	Methodology of research work	8-9
7	Expected outcome	9-10
8	References	10-12

1. Introduction

HAYNES HR-160 is a nickel–cobalt–chromium–silicon–based high-temperature alloy engineered for service in extremely corrosive and thermally severe environments. It is widely utilized in chemical process equipment, aerospace hardware, metallurgical furnace components, gas turbine sub-assemblies, incineration systems, and heat-resistant applications where exceptional structural stability and oxidation resistance are required. The alloy's unique combination of sulfidation resistance, carburization resistance, molten salt corrosion resistance, and superior oxidation tolerance at elevated temperatures makes it a preferred material for components exposed to aggressive thermal and chemical environments.

Despite these advantages, HAYNES HR-160 presents significant manufacturing challenges due to its complex metallurgical composition and inherent mechanical properties. Its high strength at elevated temperatures, low thermal conductivity, work-hardening tendency, and chemical affinity for tool materials lead to rapid tool degradation, excessive heat generation, poor chip formation, and dimensional inaccuracies during conventional machining operations. These limitations not only increase machining cost and time but also restrict the manufacturability of intricate geometries often required in high-performance engineering applications.

In this context, Die-sinking Electrical Discharge Machining (EDM) has emerged as a viable non-traditional machining technology for electrically conductive superalloys such as HR-160. EDM removes material through a series of controlled electrical discharges occurring between the tool electrode and workpiece in the presence of a dielectric fluid. This non-contact thermal erosion mechanism eliminates cutting forces and avoids mechanical deformation, making it suitable for machining hard, tough, and heat-resistant alloys irrespective of their mechanical characteristics. Additionally, EDM allows the fabrication of complex cavities, 3-D contours, and high-aspect-ratio features with high dimensional precision.

However, machining HR-160 through die-sinking EDM is not without challenges. The intense, localized thermal loads generated during spark erosion can result in **low material removal rate (MRR)**, **excessive tool wear rate (TWR)**, and the formation of undesirable surface features such as **recast layers, micro-cracks, micro-voids, and globules**. These defects may deteriorate mechanical reliability, reduce fatigue life, and compromise the functional performance of HR-160 components used in high-temperature service. The machining behavior of HR-160 under EDM is further influenced by a complex interplay of process parameters including pulse-on time, discharge current, pulse-off time, dielectric flushing pressure, and electrode material.

Given these challenges, a comprehensive investigation into the machinability characteristics of HAYNES HR-160 using die-sinking EDM is essential. Such a study will contribute to understanding the fundamental spark-material interactions and surface integrity responses unique to this alloy. Moreover, advanced modeling techniques—including statistical analysis, Response Surface Methodology (RSM), and Artificial Intelligence (AI) tools—can provide predictive insights into machining outcomes, enabling the formulation of optimal machining strategies.

This research therefore aims to systematically investigate the machining behavior of HAYNES HR-160 under die-sinking EDM by examining its performance characteristics, analyzing microstructural alterations, developing predictive models, and optimizing process parameters. The knowledge generated will support industries in achieving high-quality machining outcomes, improved efficiency, and enhanced reliability in manufacturing HR-160 components for critical high-temperature applications.

2. Review of Literature

Existing literature provides a substantial body of research on Electrical Discharge Machining (EDM) of nickel-based superalloys such as Inconel 718, Inconel 625, Inconel 686, and MAR-M247, owing to their extensive use in aerospace, power generation, and high-temperature engineering applications. Numerous studies have established that EDM performance in these materials is highly sensitive to process variables including discharge current, pulse-on time, pulse-off time, dielectric flushing pressure, and electrode material. These parameters collectively govern key machinability outcomes such as Material Removal Rate (MRR), Tool Wear Rate (TWR), Surface Roughness (SR), and recast layer morphology. Research using Inconel and MAR-M series alloys consistently highlights that increased discharge energy enhances MRR but also leads to thicker recast layers, deeper micro-cracks, and increased electrode wear due to intensified thermal loading.

Methodologically, several researchers have employed Taguchi Design of Experiments (DOE), Response Surface Methodology (RSM), and Analysis of Variance (ANOVA) to statistically analyze the influence of process parameters and to develop empirical models for predicting machining responses. Advanced computational techniques such as Artificial Neural Networks (ANN), Adaptive Neuro-Fuzzy Inference Systems (ANFIS), and hybrid machine-learning models have also been used to improve prediction accuracy and optimize multi-response machining scenarios. These approaches have proven effective in establishing parametric relationships and optimizing conflicting objectives such as maximizing MRR while minimizing TWR and SR.

Despite broad research on other nickel-based superalloys, there exists a notable scarcity of literature focusing specifically on die-sinking EDM machining of **HAYNES HR-160**. This alloy possesses a distinctive cobalt–chromium–silicon-enriched microstructure, which exhibits different thermal, metallurgical, and erosive behavior under EDM conditions compared to more commonly studied Inconel grades. The alloy's strong resistance to high-temperature degradation and chemical attack significantly alters its response to spark-induced melting, resolidification, and plasma-driven thermal cycling. Consequently, generalizations from studies on Inconel 718, Inconel 686, or MAR-M247 are inadequate for predicting the machinability of HR-160.

The limited literature highlights several critical research gaps that must be addressed to fully understand EDM behavior of HR-160, including:

• **Detailed surface integrity assessment**, particularly regarding recast layer formation, micro-cracks, and heat-affected zone characteristics.

• **Comprehensive microstructural characterization** using SEM, EDS, XRD, and microhardness analysis to understand thermal damage and material transformations.

• **Comparative studies of electrode performance**, as electrode–material interactions may differ significantly due to the alloy's cobalt-rich matrix.

• **Development of predictive AI-based models**, which are absent for HR-160 despite their proven effectiveness for other superalloys.

• **Optimization frameworks tailored to HR-160**, since its thermal behavior and erosion characteristics necessitate unique optimization strategies.

Given these gaps, there is a clear need for a **systematic and comprehensive machinability analysis** of HAYNES HR-160 using die-sinking EDM. Addressing these issues will not only expand scientific understanding but also support industries that rely on HR-160 for high-temperature, corrosion-critical, and performance-sensitive applications.

3. Objective of the Study

Primary Objective

The primary objective of this research is to conduct a comprehensive, systematic, and scientifically grounded analysis of the machinability characteristics of HAYNES HR-160 alloy during die-sinking Electrical Discharge Machining (EDM). The study aims to develop an optimized machining framework that enhances performance efficiency, improves surface integrity, and ensures precision and reliability suitable for high-temperature industrial applications

Specific Objectives

1. To experimentally investigate the influence of key EDM parameters on MRR, TWR, surface roughness, and dimensional accuracy when machining HR-160.

This objective involves assessing how variations in fundamental EDM input parameters—such as discharge current, pulse-on time, pulse-off time, servo voltage, and dielectric flushing pressure—affect critical machinability responses. The experimental work will quantify the direct and interactive effects of these parameters on material removal efficiency, electrode wear behavior, surface quality, and dimensional precision. The outcomes will help identify optimum operating windows and understand energy–material interactions specific to HR-160.

2. To examine microstructural alterations—including recast layer thickness, micro-cracks, heat-affected zones, and hardness variations—using SEM, EDS, and XRD.

This objective addresses the need for detailed characterization of EDM-induced surface and subsurface changes. Advanced microscopy and spectroscopy techniques such as Scanning Electron Microscopy (SEM), Energy-Dispersive Spectroscopy (EDS), and X-Ray Diffraction (XRD) will be used to analyze crater morphology, elemental diffusion, phase transformations, and thermal damage. Microhardness measurements will reveal mechanical property gradients within the heat-affected zone (HAZ). This comprehensive analysis will provide insights into the thermal behavior of HR-160 under discharge conditions.

3. To compare the machining performance of different electrode materials such as copper, and graphite.

This objective aims to evaluate the influence of electrode material properties—thermal conductivity, melting point, electrical conductivity, and wear resistance—on EDM machining behavior. Through controlled experiments using copper, graphite, copper-tungsten, and potentially other hybrid electrodes, the study will identify the most suitable electrode for achieving high MRR, low TWR, superior surface finish, and stable machining performance. The comparison will offer material-specific guidelines for industrial EDM applications involving HR-160.

4. To develop predictive models using statistical tools and AI-based approaches (ANN, ANFIS, or machine learning).

This objective focuses on creating accurate predictive frameworks that can estimate machining performance based on input parameter settings. Statistical modeling techniques such as regression analysis and RSM will be complemented with advanced AI methodologies including Artificial Neural Networks (ANN), Adaptive Neuro-Fuzzy Inference Systems (ANFIS), and machine learning algorithms. These models will enhance the ability to predict MRR, TWR, surface roughness, and microstructural outcomes with high accuracy and generalization capability.

5. To optimize key machining responses using suitable multi-objective optimization methods.

Since EDM performance involves multiple conflicting objectives—such as maximizing MRR while minimizing TWR and surface roughness—this objective aims to employ multi-objective optimization techniques. Approaches such as Grey Relational Analysis

(GRA), Multi-Objective Evolutionary Algorithms, TOPSIS, MOORA, or NSGA-II will be used to identify optimal parameter combinations. The optimization will ensure balanced machining performance, greater productivity, and enhanced surface integrity.

6. To propose a machinability index specifically designed for die-sinking EDM of HAYNES HR-160.

This objective seeks to develop a unified machinability index that integrates various machining performance measures—MRR, TWR, Ra, recast layer characteristics, and energy efficiency—into a single quantitative metric. The index will serve as a practical tool for benchmarking machinability, comparing electrode materials, and evaluating EDM setups. It will also provide industries with a standardized approach for assessing EDM performance on HR-160 and similar high-temperature alloys.

4. Significance of the Study

i. Industrial Relevance and Practical Applicability

This study directly addresses the long-standing industrial challenge of machining HAYNES HR-160—a high-temperature, corrosion-resistant alloy widely used in aerospace, chemical processing, and thermal engineering sectors. By developing optimized EDM strategies, the research supports more efficient and reliable manufacturing of HR-160 components for demanding service environments.

ii. Scientific Contribution to EDM Mechanisms

The work deepens scientific understanding of spark-eroded surface characteristics, thermal damage mechanisms, and alloy-specific responses unique to HR-160's cobalt-chromium-silicon microstructure. Insights into recast layer formation, micro-crack development, and thermal degradation advance the fundamental knowledge of EDM's interaction with high-temperature superalloys.

iii. Advancement in Modelling and Optimization

By integrating predictive modeling techniques—statistical, AI-based, and multi-objective optimization frameworks—the study enhances process predictability and fosters data-driven decision-making. These models will help industries and researchers forecast machining performance and minimize trial-and-error experimentation.

iv. Enhanced Productivity and Component Quality

The findings will offer practical guidelines to industries aiming to improve machining productivity, reduce tool wear, and achieve superior surface finish. Improved process control and optimized parameter settings will contribute to longer component life and greater operational reliability of HR-160 parts used in extreme conditions.

v. Contribution to Non-Traditional Machining Research

The research strengthens the body of knowledge on die-sinking EDM, particularly for advanced superalloys that remain underexplored. By establishing machining behavior insights and optimized frameworks for HR-160, the study supports the development

of next-generation high-temperature superalloy components and advances modern manufacturing technologies.

5. Study Area

The research will be carried out across three key facilities that collectively support the experimental, analytical, and computational components of the study:

i. Experimental

This facility will be utilized for conducting all die-sinking EDM experiments on HAYNES HR-160. It provides access to EDM machines, electrodes, dielectric systems, and precision measurement tools required for controlled machining trials and performance evaluation.

ii. Materials Characterization

Advanced surface and subsurface analyses will be performed in this lab using characterization instruments such as SEM, EDS, XRD, and microhardness testers. These tools will enable detailed examination of recast layers, micro-cracks, thermal damage, elemental distribution, and phase transformations resulting from EDM machining.

iii. Computational

This facility will support statistical modeling, numerical simulation, and the development of AI-based predictive frameworks. Software for DOE, RSM, ANOVA, ANN/ANFIS modeling, and optimization will be employed to analyze experimental data and derive predictive insights.

Together, these integrated facilities provide a comprehensive environment for executing the experimental, microstructural, and computational aspects of the research in a cohesive and scientifically rigorous manner.

6. Methodology of Research Work

Phase 1: Literature Survey and Problem Identification

Comprehensive review to identify research gaps, select parameters, responses, and experimental strategy.

Phase 2: Experimental Design

Selection of input parameters:
• Current

• Pulse-on time
• Servo voltage

DOE using Taguchi/RSM/CCD based on required precision.

Phase 3: Machining Experiments

Conduct die-sinking EDM trials on HR-160 specimens using different electrodes.
Measure MRR, TWR, SR, and dimensional deviation.

Phase 4: Surface Integrity and Microstructural Analysis

• SEM and optical microscopy for crater morphology and micro-cracks
• EDS for elemental diffusion
• XRD for phase transformations and residual stress
• Microhardness for HAZ profiling

Phase 5: Modelling and Prediction

• Regression analysis
• ANN/ANFIS/ML-based prediction models
• Model validation through R^2, RMSE, and confirmation tests

Phase 6: Multi-objective Optimization

Use of techniques such as GRA, TOPSIS, MOORA, or evolutionary algorithms to determine optimal EDM conditions.

Phase 7: Development of Machinability Index

Integration of multiple responses into a unified scoring system for industrial evaluation.

Phase 8: Validation and Thesis Preparation

Final validation experiments, documentation, and result integration.

7. Expected Outcome

i. Development of a Comprehensive EDM Machinability for HR-160

The study will produce a detailed machinability map illustrating the relationship between key EDM parameters and machining responses. This map will help identify optimal operating windows and serve as a reference for industrial machining of HR-160.

ii. Optimized Process Parameters for Enhanced Performance

Through experimental evaluation and multi-objective optimization, the research will establish the best parameter settings for achieving higher MRR, reduced TWR, and improved surface finish, ensuring efficient and high-quality EDM machining.

iii. In-depth Understanding of Microstructural and Thermal Effects

The investigation will generate valuable insights into EDM-induced microstructural changes, including recast layer characteristics, micro-crack formation, elemental diffusion, and heat-affected zones, enabling a clearer understanding of thermal-erosive mechanisms in HR-160.

iv. Development of Accurate AI-Based Predictive Models

Advanced predictive models based on AI and statistical techniques will be developed to accurately forecast machining performance. These models will support intelligent parameter selection and process automation.

v. Contribution to High-Quality SCI/Scopus Publications

The comprehensive findings, including experimental results, surface integrity evaluation, optimization outcomes, and AI-based modeling, are expected to lead to multiple publications in reputable SCI/Scopus-indexed journals, strengthening academic and industrial knowledge.

8. References

1. Aneesh, T., Mohanty, C. P., Tripathy, A. K., Chauhan, A. S., Gupta, M., & Annamalai, A. R. (2023). A thermo-structural analysis of die-sinking electrical discharge machining (EDM) of a Haynes-25 superalloy using deep-learning-based methodologies. Journal of Manufacturing and Materials Processing, 7(6), 225.
2. Haynes International. (2024). HAYNES HR-160 alloy – High-temperature corrosion-resistant alloy datasheet. https://haynesintl.com/wp-content/uploads/2024/08/hr-160.pdf
3. Mohanty, C.P.; Sahu, J.; Mahapatra, S.S. Thermal-structural analysis of electrical discharge machining process. Procedia Eng. 2013, 51, 508–513.
4. Joshi, S.N.; Pande, S.S. Thermo-physical modeling of die-sinking EDM process. J. Manuf. Process. 2010, 12, 45–56.
5. Jithin, S.; Raut, A.; Bhandarkar, U.V.; Joshi, S.S. FE modeling for single spark in EDM considering plasma flushing efficiency. Procedia Manuf. 2018, 26, 617–628.
6. Singh, H. Experimental study of distribution of energy during EDM process for

utilization in thermal models. Int. J. Heat Mass Transf. 2012, 55, 5053–5064.

7 Tiwari, A.K.; Dvivedi, A.; Pal, K. Thermal modeling of EDM process using FEA and parametric study of MRR. In AIP Conference Proceedings; AIP Publishing LLC: New York, NY, USA, 2021; Volume 2341, p. 040042.

8 Patel, I.; Powar, P. FEM analysis with experimental results to study the effect of EDM parameters on MRR of AISI 1040 steel. Int. Res. J. Eng. Technol. 2018, 5, 1332.

9 Kumar, S.; Das, S.; Joshi, S.N. Finite Element Modeling of Thermal Residual Stresses generated during EDM of AISI 1018 Steel. J. Inst. Eng. 2021, 103, 29–37.

10 Machine, P.M.E.D. Development of a Thermo-physical model of powder mixed electrical discharge machine using FEM and experimental validation. Int. J. Adv. Eng. Technol. 2014, 107, 111.

11 Mohanty, C.P.; Mahapatra, S.S.; Sahu, J. Parametric optimization of electrical discharge machining process: A numerical approach. Int. J. Ind. Syst. Eng. 2016, 22, 207–244.

12 Jilani, S.T.; Pandey, P.C. An analysis of surface erosion in electrical discharge machining. Wear 1983, 84, 275–284.

13 Halkaci, H.S.; Erden, A. Experimental investigation of surface roughness in electric discharge machining (EDM). In Proceedings of the 6th Biennial Conference on Engineering Systems Design and Analysis, Ystanbul, Turkey, 8–12 July 2002; pp. 8–11.

14 Amorim, F.L.; Weingaertner, W.L. Die-sinking EDM of AISI P20 tool steel under rough machining using copper electrodes. In Proceedings of the 2o. COBEF-Congresso Brasileiro de Engenharia de Fabricação, Brasilia, Brazil, 10–12 May 2003; pp. 18–21.

15 Mohanty, A.; Talla, G.; Gangopadhyay, S. Experimental investigation and analysis of EDM characteristics of Inconel 825. Mater. Manuf. Process. 2014, 29, 540–549.

16 Joshi, S.; Govindan, P.; Malshe, A.; Rajurkar, K. Experimental characterization of dry EDM performed in a pulsating magnetic field. CIRP Ann. 2011, 60, 239–242.

17 Dastagiri, M.; Kumar, A.H. Experimental Investigation of EDM Parameters on Stainless Steel&En41b. Procedia Eng. 2014, 97, 1551–1564.

18 Dvivedi, A.; Kumar, P.; Singh, I. Experimental investigation and optimisation in EDM of Al 6063 SiCp metal matrix composite. Int. J. Mach. Mach. Mater. 2008, 3,

293–308.

19 Prasad, A.R.; Ramji, K.; Datta, G.L. An experimental study of wire EDM on Ti-6Al-4V alloy. Procedia Mater. Sci. 2014, 5, 2567–2576.

20 Palanisamy, D.; Devaraju, A.; Manikandan, N.; Balasubramanian, K.; Arulkirubakaran, D. Experimental investigation and optimization of process parameters in EDM of aluminium metal matrix composites. Mater. Today Proc. 2020, 22, 525–530.